

Digital Addressable Control Module

MODEL: PX-DA-CM

Addressable Control modules are used to supervise a circuit of dry-contact output devices. PX-DA-CM offers a single input dry contact for integration any third party devices not connected with Fire Alarm panel. PX-DA-CM is available with back box so that the device can be semi-flush or surface mounting.

Features:

- **Wall mount facility**
- **Suitable for malls, restaurant, residential etc.**

Operation:

PX-DA-CM addressable monitor Module is designed to transmit normally open switch signal to any devices with coincidence functions, and transmits messages from fire alarm control panel (FACP) with coincidence detection function.

Features:

- **Unique 'Plug & Play' installation concept**
- **Digital addressable communications**
- **Multiple contacts module is available (optional)**
- **Semi-Flush or surface Mounting**
- **For Semi Flush mounting back box is available with module**
- **Used to interface devices like AHU, filt control, PA system etc.**
- **Compatibility with ASES digital addressable FACP**
- **Wall mount facility**



Specification:

Operating voltage	24V DC
Relay Control rating	7 Amp @ 240 VAC/7Amp. 24Vdc
Current Consumption (Fire)	250µA @ 24 VDC
Application Temp Range	0° C to + 60° C
Humidity	5-95% Relative Humidity (non condensing)
Housing	ABS
Weight	80gm
Dimensions (mm)	100 x 93 x 53 (W x H x D)
Colour	White

Ordering Information:

Part Number	Pack Quantity	Dimensions (WxHxD millimetres)	Weight
PX-DA-CM	Individual(1 units)	110 x 110 x 60	100g