ASES SECURITY PVT. LTD.
AN ISO 9001:2015 CERTIFIED COMPANY
CIN: U32109DL 2006PTC156438

PA AMPLIFIER AS-350-DP



FEATURES & FACILITIES

- 220-240V AC & 24V DC operation.
- 6 MIC & 2 AUX input.
- Built in MP3 player with remote control for USB, SD/MMC card reader,
- FM player & Bluetooth.
- Preamplifier & Line output for connecting to a Booster Amplifier.
- Preout for recording the programme.
- Instant transfer to DC power (Car Battery) if AC power fails.
- Bass & Treble tone controls Cut type.
- Echo with delay & repeat effects in all 3 Mics.
- Line input for connecting the output from any external mixer or preout
- SSA-350 to be used as a booster power amplifier.
- Bass boost defeated at driver unit position for safer operation of driver units
- Adjustable echo volume
- 20-250 mili second delay time.

TECHNICAL SPECIFICATION

POWER OUTPUT	350W RMS @10% THD 450W MAX
INPUT CHANNELS	6 X MIC 0.65mV/4.7kΩ 2 X AUX 100mV.470kΩ 1 X LINE 1V/50KΩ
FREQUENCY RESPONSE	50-15000Hz ±3dB
SIGNAL TO NOISE RATIO	60dB
TONE CONTROLS	Bass ±10dB at 100Hz Treble ±10dB at 100Hz
Preamp output Line Output	200mV/600Ω 1V/ 1kΩ
Speaker Output	4Ω, 8Ω (For direct connection) 70V & 100V: Line (For use with LMT)
Power Supply	AC: 220-240 Volts 50/60 Hz DC: 24V
AC POWER CONSUMPTION	610 VA
DC POWER CONSUMPTION	12 A
DIMENSIONS (LXBXH)	W- 480 x H-165 x D-340 (Approx)
ECHO DELAY TIME	30-25 MILI SECOND
NET WEIGHT	15.700 kg (Approx)