

PA AMPLIFIER DPA-75WATT

PA AMPLIFIER
DPA-75WATT



FEATURES & FACILITIES

- 220-240V AC & 12V DC Operation.
- 4 MIC & AUX input.
- Built-in MP3 pleyer with remote control for USB, SD/MMC card reader, FM pleyer & Bluetooth.
- Line output for connecting to a Booster Amplifier.
- Preout for recording the programme. Instant transfer to DC power (Car Battery) if AC power fails.
- Bass & Treble tone control Cut & Boost type.
- Echo with Delay & Repeat Effects in all 4 Mics.

TECHNICAL SPECIFICATION

POWER OUTPUT	75W RMS @ 10%THD 105W MAX
INPUT CHANNELS	4 x MIC 0.60mV/4.7k Ω 1 x AUX 100mV/470k Ω
FREQUENCY RESPONSE	50- 15000Hz $\pm$ 3dB
SIGNAL TO NOISE RATIO	60dB
TONE CONTROLS:	Bass $\pm$ 10db at 100Hz Treble $\pm$ 10db at 10kHz
Preamp output Line Output	200mV/60 Ω 1V/ 1k Ω
Output Taps for Speaker Matching	4 Ω , 8 Ω & 16 Ω (For Direct Connection) 70V & 100V: Line (For use with LMT)
Power Supply	AC : 220-240 Volts 50/60 Hz DC: 12V
AC POWER CONSUMPTION	180 VA
DC POWER CONSUMPTION	3 A
NET WEIGHT	7 KG. APPROX.
Dimensions	W- 380 x H-150 x L-310 (Approx)