


PARKING FANCING BARRIER

Model : AS-PFB



Rebound Function
in Resistance




1.8s Quick
Lifting speed



Long remote
Control Range-30m



Negligible
Maintenance



24V DC
Brushless Motor

FEATURES

- The gate movement adopts a crank shaker drive mechanism which has a compact structure, enhanced rigidity, and convenient maintenance and operation.
- When the gate rod is in the horizontal or vertical state, the movement structure is completely self-lock, which can effectively protect the reducer from external force impact.
- Compared with ordinary gate movement, the parts are reduced by about 20% and the faults are less.

TECHNICAL SPECIFICATION

| | |
|-------------------------|--|
| Appearance Dimension | 340mm * 272mm * 1000mm |
| Power Supply | 220V \pm 10% 50 ~ 60Hz |
| Voltage | AC110V/220V |
| Motor | 24v150w brushless 2-stage variable speed all copper DC motor |
| Remote Control Distance | \leq 30m |
| Waterproof Grade | IP45 |
| Working Environment | -15°C ~ +70°C |
| Box Thickness | Full-thickness 1.5mm |
| Open Time | 6 Sec |
| Motor Capacity | 24V DC Brushless Motor |
| Boom Length | 3 to 6m |

DIMENSIONS

