

INTELLIGENT ADDRESSABLE WALL SOUNDER BEACON

Model : AS-901-CWSV+AS-901-WSM

PRODUCT INFORMATION

The AS-901-CWSV+AS-901-WSM is an Series-900 intelligent analogue addressable Wall Sounder Beacon that combines wall sounder beacon and addressable interface module. The Sounder beacon is for indoor use and is equipped with 4 recognized tones which can be locally at the sounder, using DIL Switches 1 & 2.

The addressable wall sounder beacon is part of Series-900 Intelligent Analog Addressable Fire Detection and Alarm System.

Once installed on to the loop the device is fully addressable and benefits from an extensive range of intelligent control and monitoring functionality.

The AS-901-CWSV+AS-901-WSM have soft addressing capability and is programmed using a handheld programmer.



FEATURES

- Sounder beacon with Series-900 with sounder interface module fitted
- 1 - 240 address range
- Intelligent digital communication protocol
- Integrated short circuit isolator
- Loop powered
- 4 Tone Settings
- Two stage alarm capability
- Programmable through handheld Programming Tool.

Approval/Certified

- EN 54-3 and EN 54-13

TECHNICAL SPECIFICATION

Loop voltage range	20Vdc – 30Vdc
Activated current load: (High Vol.)	10-280 mA at 28 Vdc
Acoustic Frequency range	400-2900 Hz
Maximum acoustic Output	97.5 dB@ 1m
Flasher signal frequency	0.5 Hz or 1 Hz
Operating temperature range	-10°C to +55°C
Unit weight (inc Back box)	254g
Max humidity (non-condensing)	95% RH
Ingress Protection	Type A-Indoor use/IP21C.
Colour	Red
Case material	ABS and PC- Flame Retardant rating IL94V2

ORDERING INFORMATION AS-901-CWSV+AS-901-WSM - ADDRESSABLE WALL SOUNDER BEACON (RED)

FACTORY PART CODE : IND -CWSV+IND-WSM