



# Public Address and Voice Alarm Systems (PAVA)

Public Address and Voice Alarm systems allow safe and controlled building evacuation to be managed in the case of an emergency. Clear voice messages can be initiated from the system to aid building evacuation.


AS-301-PAVA




- 8/16 Zone LEDS Indication/ Paging Control Unit for use with AS-301-Selector.
- AS-301-PA is a rack mounting switcher / control unit which works with AS-301-Selector and upto 1 amplifiers to form 8/16 zone zonal paging system.
- Provision for one 100V input signals, for speech.
- Provision to make announcements from the control unit. In case of 8/16 zone system using Inns. AS-301-PA control unit, announcements should be made only from the master control unit.
- Status monitoring ofall zones with LEDS Indication.
- Provision for emergency trigger input and alarm input with highest priority.
- Standard 19" rack mounting chassis.
- Automatic voice plays incase of triger through pen drive.



- A high performance 8/16 zone paging console housed in an elegant aluminium housing. Itworks with As-301-PA tomake a 8/16 zone zonal paging system.
- Fitted with a 16"(40 cm) gooseneck.
- 8/16 Zone Selector Switches, plus ALL CALL switch
- Separate Mic ON/OFF switch.
- LED indication of zone selection.
- Securespin and 2 Nos lockable connectors.
- Can be used withone AS-301-PA tomakealozone paging system
- Operates on 24V DC supply from AS-301-PA





### **PANEL**

- Modular design, plug in type solid state.
- Tested by ERTL as per IS: 2189.
- Expandable up to 2 to 64 zones.
- Gooseneck mic attached for call to sub stations. Zone wise selector switch and all switch facility with Digital Selector keypad.
- Music player attachable facility optional.
- Simple integration with Fire Alarm Panels to activate. EVAC/ALERT pre-recorded messages. (Optional)
- Inbuilt battery charger and battery space.
- Customized Talk back Unit. (Optional).
- Used for 1-way communication.
- Amplifier wattage can be customized depending upon requirements.
- Simple to connect speaker cum Talk back slave
- Press and talk facility.
- Max line length is 300 m with 1.5mm cable.













## **Ceiling** Loudspeaker

Fully ABS plastic with metal grille

Power tapping options available -6/3/1.5W

Rated Power / Max Power

**Power Taps** 

**Rated Voltage** 

Sound Pressure Level

**Rated Impedance** 

**Frequency Response** 

SPL at rated power/1W

Color

6W/9W

6w/3w/1.5w

100 V

90 ± 5 dB at 1w (1m& 1kHz)

1667Ω/ 3333Ω/ 6666Ω

125Hz - 16kHz

(-10 dB with reference to 1kHz)

95dB/88dB (1m & 1kHz) White



P.A. Wall **Mount Speaker**  12 Watt Full Range Speaker

- Colour white ABS plastic box
- Slim speaker
- Equipped with the transformer to provide 100V AC
- Power tap selection 3W/6W/12W

**Operating Voltage** 

Max. Power

**Power Taps** 

Freq. Resp.

**Sound Pressure Level** 

70-100V AC


**12 W RMS** 

3W/6W/12W

150-15K Hz

90-95 dB @ 100V, 1m.





#### **Head Office**

301, Aggarwal Tower, L.S.C-II, Mandawali, Patparganj, Delhi-110092

Off. & Works - Unit 1 ASES HOUSE, A-2 / 69 Site-IV, Sahibabad Indl. Area , Ghaziabad, U.P.-201010

Off. & Works - Unit 2 Plot No. 52, Toy City, Ecotech III, Greater Noida, Uttar Pradesh 201306

#### Kolkata Office

Mira Bhawan, 250, Block-B, Laketown, Ground Floor, Kolkata-700089

#### **Bangalore Office**

No – 18, 2nd Floor, Matadahalli, Further Extensions, R. T. Nagar, Next Building to Himalaya, Bangalore – 560032

#### Mumbai Office

17/A-4, Shiv Shakti Industrial Estate, Opp. Damodar Park, LBS Marg, Ghatkopar (W), Mumbai - 400086