

## Digital Addressable Control Module

MODEL: PX-DA-CM

Addressable Control modules are used to supervise a circuit of dry-contact output devices. PX-DA-CM offers a single input dry contact for integration any third party devices not connected with Fire Alarm panel. PX-DA-CM is available with back box so that the device can be semi-flush or surface mounting.

### Features:

- **Re-settable operation**
- **Wall mount facility**
- **Suitable for malls, restaurant, residential etc.**

### Operation:

PX-DA-CM addressable monitor Module is designed to transmit normally open switch signal to any devices with coincidence functions, and transmits messages from fire alarm control panel (FACP) with coincidence detection function.

### Features:

- **Unique 'Plug & Play' installation concept**
- **Digital addressable communications**
- **Multiple contacts module is available (optional)**
- **Semi-Flush or surface Mounting**
- **For Semi Flush mounting back box is available with module**
- **Used to interface devices like AHU, firt control, PA system etc.**
- **Compatibility with ASES digital addressable FACP**
- **Wall mount facility**



## Specification:

Operating voltage	<b>24V DC</b>
Control rating	<b>7 Amp @ 240 VAC</b>
Current Consumption (Normal /Fire)	<b>150µA 60mA @ 24 VDC</b>
Application Temp Range	<b>0° C to + 60° C</b>
Humidity	<b>5-95% Relative Humidity (non condensing)</b>
Housing	<b>ABS</b>
Weight	<b>80gm</b>
Dimensions (mm)	<b>100 x 93 x 53 (W x H x D)</b>
Colour	<b>White</b>

## Ordering Information:

Part Number	Pack Quantity	Dimensions (WxHxD millimetres)	Weight
PX-DA-CM	Individual(1 units)	110 x 110 x 60	100g